



Multifunktionales 15" / 1" System mit sehr breitbandigem Frequenzumfang und ausgewogener Klangcharakteristik. Ähnliche Eigenschaften wie die A 6, jedoch mit tieferreichender Basswiedergabe, machen die A 8 zu einem universellem Fullrangewerkzeug. Diverse M8 und M10 Aufnahmepunkte sorgen für die einfache Montage des Zubehörs. Auch als Festinstallationsvariante lieferbar.

PRODUCT SPECIFICATIONS

Speaker Components	15" Nd / 1"
Description	Multi Purpose Sound System
Power AES / Peak	500 W / 1500 W
Impedance nominal	8 Ω
SPL 1 W / Peak @ 1 m	99 dB / 131 dB
Usable Range	50 Hz - 20 kHz (-10 dB)
Tuning Frequency Excursion minimum	50 Hz
X - Overpoint acoustical	1,3 kHz
Coverage horizontal / vertical	90° x 60° - rotatable
Connectors	2 x Speakon NL4MP in/out Coding: 1 +/- HiMid, 2 +/- loop thru
Handles	2 x
Rigging / Fittings	2 x M10 / 7 x M8 35 mm pole mount
Weight	23,5 kg
Size height x width x depth	69,8 x 45,0 x 42,5 cm
Order No.	00270/II 00270/AF/II (installation version)



Die 35 mm Flanschhülse wurde in den Griff integriert.



Technical drawing of the M8000 cabinet showing front, top, and side views with dimensions and mounting points.

Front View: The cabinet has a total width of 425 mm and a total height of 450 mm. The main body is 340 mm high and 180 mm wide. There are two M8 mounting points on the front panel. The top panel is 40 mm thick.

Top View: The cabinet has a total width of 698 mm and a total depth of 450 mm. The main body is 340 mm deep and 180 mm wide. There are two M8 mounting points on the top panel. The side panel is 40 mm thick.

Side View: The cabinet has a total width of 425 mm and a total height of 450 mm. The main body is 340 mm high and 180 mm wide. There are two M8 mounting points on the side panel. The top panel is 40 mm thick.

Mounting Points: The cabinet features two M8 mounting points on the front panel and two M8 mounting points on the top panel. The side panel also has two M8 mounting points. The top panel has a 45° angle on the right side.

[illegible]